

BLANK PAGE



IS: 10392 - 1982 (Reaffirmed 1994)

Indian Standard

SPECIFICATION FOR FEED WATER AND BOILER WATER FOR LOW AND MEDIUM PRESSURE LAND BOILERS

(Third Reprint OCTOBER 2008)

UDC 621.187.12:621.181-984:006.76

© Copyright 1983

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

Gr 2 March 1983

AMENDMENT NO. 1 DECEMBER 2008

IS 10392: 1982 SPECIFICATION FOR . FEED WATER AND BOILER WATER FOR LOW AND MEDIUM PRESSURE LAND BOILERS

[Page 5, Table 1, Sl No (i)(d)] — Insert the following after (d):

'e) Residual hydrazine 0.1 to 1 0.1 to 0.5 0.05 to 0.3 26 (as N₂H₄), mg/l (if added) (if added)

[Page 5, Table 1, Sl No. (ii)(f)] — Delete the row.

(Page 6, Note 2) — Substitute the following for the existing:

"NOTE 2 — When feed water heaters are of non-ferrous constructions, the pH of the feed water should be maintained between 8.8 and 9.0 while when feed water heaters are of iron construction, the pH of the feed may be maintained between 9.0 and 9.2."

Indian Standard

SPECIFICATION FOR FEED WATER AND BOILER WATER FOR LOW AND MEDIUM PRESSURE LAND BOILERS

Boiler Water Sectional Committee, CDC 57

Chairman

Representing

SHRI P. C. D. G. SAMUEL

Madras Refineries Ltd, Madras

Members

SHRI J. N. BHOWMIK West Bengal State Electricity Board, Calcutta

SHRI A. K. SANTRA (Alternate)
SHRI D. CHATTERJER Delta Enterprises Pvt Ltd, Calcutta

DEPUTY DIRECTOR (CM), Railway Board (Ministry of Railways)

RDSO, LUCKNOW

ASSISTANT CHEMIST & METAL-

LURGIST, WR, BOMBAY (Alternate)

SHRI DEV RAJ Power Engineers Training Society, New Delhi

DR N. DEVARAJAN Industrial and Agricultural Engineering Co
(Bombay) Ltd, Bombay

SHRI S. C. DEY Ministry of Industry (Department of Industrial

Development), New Delhi

SHRI SHOMNATH GHOSH Jai Guru Engineering Co (India), Calcutta Shri Anandamay Ghosh (Alternate)

DR A. K. GUPTA Hindustan Fertilizer Corporation Ltd, Durgapur

Unit, Durgapur Suri A. K. Sengupta (Allernate)

SHRI G. T. JADEJA The Tata Hydro-Electric Power Supply Co Ltd.
Bombay

SHRI G. M. RAWAL (Alternate)

SHRI J. JHA Central Electricity Authority, New Delhi DR V. M. KELKAR Engineers India Ltd, New Delhi

SHRI G. L. RAJANI (Alternate)

SHRI K. R. KRISHNASWAMY Central Power Research Institute, Bangalore Shri P. S. RAJALAKSHMI (Alternate)

Shri N. Krithiyasan Central Electrochemical Research Institute (CSIR),

Karaikudi Shri T. M. Balabubramanjan (Alternate)

SHRI S. MAHADEVAN Chemical Consultants, Madras

SHRIC. S. RAGHAVAN (Alternate)

(Continued on page 2)

© Copyright 1983

BUREAU OF INDIAN STANDARDS

This publication is protected under the *Indian Copyright Act* (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

IS: 10392 - 1982

(Continued from page 1)

Members	Representing					
DR P. K. MATHUR	Bhabha Atomic Research Centre, Bombay					
SHRI R. NATARAJAN SHRI T. R. NAGARAJAN (Alle	Bharat Heavy Electricals Ltd, Hyderabad					
DR A. PRABHAKAR RAO (All						
SHRI R. NATARAJAN	Hindustan Dorr-Oliver Ltd, Bombay					
Suri Subasu Verma (Alterna	ile)					
SHRI RAM GOPAL	National Thermal Power Corporation Ltd, New Delhi					
SHRI R. K. DWIVEDT (Alternat	e)					
	Ion Exchange (India) Ltd, Bombay					
Shri S. Chandrasekhar (Al	ternate)					
Dr S. K. Roy	The Alkali & Chemical Corporation of India Ltd, Calcutta					
DR V. K. SETH Projects & Development India Ltd, Sindri						
SHRI S. K. SHOME						
SHEER, N. BANERJEN (Alternate)						
Sum D. P. Singh	Delhi Electric Supply Undertaking, New Delhi					
Shri K. B. Chhabra (Alterna	te)					
SHRI G. P. SINGH SHRI A. P. SINHA (Alternate)	Steel Authority of India Ltd, New Delhi					
SHRI S. K. M VTHUR, Head (Chem)	Director General, ISI (Ex-officio Member)					

Secretary

SHRI A. K. BAHL Assistant Director (Chem), ISI

Indian Standard

SPECIFICATION FOR FEED WATER AND BOILER WATER FOR LOW AND MEDIUM PRESSURE LAND BOILERS

O. FOREWORD

- **0.1** This Indian Standard was adopted by the Indian Standards Institution on 31 December 1982, after the draft finalized by the Boiler Water Sectional Committee had been approved by the Chemical Division Council.
- **0.2** Boilers require good quality water for their safe and efficient operation. Natural water accumulates impurities rendering it unfit for use in boilers without treatment. Though water treatment is costly, in the long run it is economic in terms of fuel and time savings. Treated water also increases safety of boilers during operation.
- 0.3 This standard lays down the specifications for feed water and boiler water for low and medium pressure land boilers while IS: 1680-1982* deals with the chemical methods of attaining the conditions to be aimed at for water for land boilers in order to overcome the troubles on the water side of boilers operating up to 2.0 MN/m² (20 kgf/cm²) pressure. IS: 1680-1982* is also generally applicable to boilers operating under medium pressure, that is, between 2.0 and 5.9 MN/m² (20 to 60 kgf/cm²) but not to marine and locomotive boilers and boilers operating at pressures higher than 5.9 MN/m² (60 kgf/cm²).
- **0.4** For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS: 2-1960†. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

^{*}Code of practice for treatment of water for low and medium pressure land boilers (third revision).

[†]Rules for rounding off numerical values (revised).

18:10392-1982

1. SCOPE

- 1.1 This standard lays down specifications for feed water and boiler water for low and medium pressure land boilers (boilers operating up to 5.9 MN/m^2).
- 1.2 Land boilers operating at pressures higher than 5.9 MN/m²; marine boilers and locomotive boilers are not covered in this standard.

2. REQUIREMENTS

2.1 The water shall comply with the requirements given in Table 1 when tested by the methods prescribed in col 6 and 7 of the table.

3. SAMPLING

- 3.1 Sampling shall be done following general directions given in 2 of IS: 3025-1964*. In particular, the following points shall be observed:
 - a) It is necessary that a stainless steel or monel metal coil is fitted on the sampling cock so that the temperature of the water sample will be well below the boiling point at atmospheric pressure and there is no risk of acration and concentration due to flashing into steam; and
 - b) Samples of fred water should be collected from the delivery of the boiler feed pump, samples of boiler water from the top drum, and samples of condensate from the delivery of the condensate extraction pump.

4. TEST METHODS

4.1 Tests shall be carried out as prescribed in the appropriate clauses of IS: 3025-1964* and IS: 3550-1965† as indicated against the characteristics in Table 1.

^{*}Methods of sampling and test (physical and chemical) for water used in industry. †Methods of test for routine control for water used in industry.

TABLE 1 CHEMICAL REQUIREMENTS OF FEED WATER AND BOILER WATER FOR LOW AND MEDIUM PRESSURE BOILERS

(Clauses 2.1 and 4.1)

SL No.	CHARACTERISTIC	REQUIREMENT FOR BOILER PRESSURE			METHOD OF TEST (REF TO CL No. OF)		
		Up to 2.0 MN/m ²	2·1 to 3·9 MN/m²	4·0 to 5·9 MN/m ²	IS : 3550- 1965*	IS: 3025- 1964†	
(1)	(2)	(3)	(4)	(5)	(6)	(7)	
i)	Feed Water						
	a) Total hardness (as CaCO ₂), mg/1, Max	10	1.0	0.5		16·1	
	b) pH value	8·5 to 9·5	8·5 to 9·5	8·5 to 9·5		8.	
	c) Dissolved oxy- gen, mg/l, Max	0.1	0.02	0.01	25		
	d) Silica (as SiO ₂), mg/l, Max	-	5	0.5	16		
ii)	Boiler Water						
	a) Total hardness (of filtered sample) (as Ca C() _a), mg l	4	-Not detectab	le	-	10-1	
	b) Total alkali- nity‡ (as Ca CO ₂), mg/l, Max	7 00	500	300	-	13	
	c) Caustic alkalinity (as Ca (X) ₃), mg/l, Max	3 50	200	60		15	
	d) pH value	11.0 to 12.0	11.0 to 12.0	10·5 to 11 0		8	
	c) §Residual sodi- um sulphite (ās Na ₈ SO ₃), mg/l	30 to 50	20 to 30	~	_	21	
	f) Résidual hydra- zine (as N ₂ H ₄), mg/l	0.1 to 1 (if added)	0·1 to 0·5 (if added)	0.05 to 0.3	26	-	
	g) Ratio Na ₂ SO ₃ / caustic alkali- nity (as Na OH)	4	above 2·5-			20.2 and 15	
	or Ratio NaNO ₃ / total alkali- nity (as Na	4	——above 0:4			48 and 13	
	OII)					(Continued)	

TABLE 1 CHEMICAL REQUIREMENTS OF FEED WATER AND BOILER WATER FOR LOW AND MEDIUM PRESSURE BOILERS — Contd

(1)	(2)	(3)	(4)	(5)	(6)	(7)
h	Phosphates (as PO ₁), mg(l (if added)	20 to 40	15 to 30	5 to 20	14	
) Total dissolved solids; mg/l, Alax	3 500¶	2 500	1 500	9	12
k) Siliçà (as SiO ₂), mg/l	Less than 0 alkalinity	r4 of causti c /	15	16	30

NOTE 1 — Recovery Boilers — The boiler feed water used should be completely demineralized and also the boiler feed water and boiler water should be conditioned in accordance with high pressure boilers working at 5.9 MN/m² (60 kg/cm²) and above (see IS: 4343-1967**).

Note 2 — When feed water heaters are of copper or copper alloy constructions, the ρ H of the feed water should be maintained between 8.5 and 9.2 while when feed water heaters are of iron construction, the ρ H of the feed may be maintained between 8.5 and 9.5.

Note 3 - Silica in Boiler Water - Lower concentration of silica may be advisable for steam of turbines, which generally require less than 0.02 mg/l silica in steam.

*Methods of test for routine control for water used in industry.

The shell type boilers depending on parameters, the limits can be relaxed.

[†]Methods of sampling and test (physical and chemical) for water used in industry. ‡Total alkalinity should preferably be about 20 percent of total dissolved solids. §Shall not apply if reducing agents other than sodium sulphite are used. ||For riveted boilers only.

^{**}Code of practice for treatment of water for high pressure boilers (under revision).

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002

Central Laboratory: Plot No. 20/9, Site IV, Sahibabad Industrial Area, SAHIBABAD 201010	Telephone 277 0032
Regional Offices:	
Central: Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002	23237617
*Eastern: 1/14 CIT Scheme VII M, V.I.P. Road, Kankurgachi, KOLKATA 700054	2337 8662
Northern . SCO 335-336, Sector 34-A, CHANDIGARH 160022	260 9285
Southern · C.I.T. Campus, IV Cross Road, CHENNAI 600113	2254 1984
†Western: Manakalaya, E9, MIDC, Behind Marol Telephone Exchange, Andheri (East), MUMBAI 400093	2832 9295
Branch Offices:	
'Pushpak', Nurmohamed Shaikh Marg, Khanpur, AHMEDABAD 380001	560 1348
Peenya Industrial Area, 1st Stage, Bangalore-Turnkur Road, BANGALORE	839 4955
Commercial-cum-Office Complex, Opp. Duehera Maidan, Arera Colony, Bittan Market, BHOPAL 462016	242 3452
62-63, Ganga Nagar, Unit VI, BHUBANESHWAR 751001	240 3139
5th Floor, Kovai Towers, 44 Bala Sundaram Road, COIMBATORE 641018	221 0141
SCO 21, Sector 12, Faridabad 121007	229 2175
Savitri Complex, 116 G.T. Road, GHAZIABAD 201001	286 1498
53/5 Ward No. 29, R.G. Barua Road, 5th By-lane, Apurba Sinha Path, GUWAHATI 781003	245 6508
5-8-56C, L.N. Gupta Marg, Nampally Station Road, HYDERABAD 500001	2320 1084
Prithavi Raj Road, Opposite Bharat Overseas Bank, C-Scheme, JAIPUR 302001	222 3282
11/418 B, Sarvodaya Nagar, KANPUR 208005	223 3012
Sethi Bhawan, 2 nd Floor, Behind Leela Cinema, Naval Kishore Road, LUCKNOW 226001	261 8923
H. No. 15, Sector-3, PARWANOO, Distt. Solan (H.P.) 173220	235 436
Plot No A-20-21, Institutional Area, Sector 52, Goutarn Budh Nagar, NOIDA 201307	240 2206
Patliputra Industrial Estate, PATNA 800013	226 2808
Plot Nos. 657-660, Market Yard, Gultkdi, PUNE 411037	2427 4804
*Sahajanand House" 3™ Floor, Bhaktınagar Circle, 80 Feet Road, RAJKOT 360002	237 8251
T.C. No. 2/275 (1 & 2), Near Food Corporation of India, Kesavadasapuram-Ulloor Road,	
Kesavadasapuram, THIRUVANANTHAPURAM 695004	255 7914
1* Floor, Udyog Bhavan, VUDA, Siripuram Junction, VISHAKHAPATNAM-03	271 2833
*Sales Office is at 5 Chowringhee Approach, P.O. Princep Street, KOLKATA 700072	2355 3243
†Sales Office (WRO) Plot No. E-9, MIDC, Rd No. 8, Behind Telephone Exchange, Andheri (East), Murnbaj-400 0093	2832 9295